

HAND PUMP

SEMI-ROTARY

The **SR** series are traditional cast iron, semi-rotary, hand-pumps. Supplied with operating handle and screwed mating flanges, they are versatile pumps suitable for water, petrol, diesel, oils, lubricants, alcohols, and non corrosive solvents. Maximum suction lift, with a foot valve is 4 metres. Can be wall mounted, permanently installed or fitted to a tank or barrel.

Static electricity may be generated by the operation of semi-rotary pumps. In order to prevent sparking caused by static build-up, when pumping flammable liquids an insulated bonding wire must be used i.e. the container must be grounded to earth by means of a conductive earthing lead, fastened between the container and a suitable grounded earth point.

SR

- ✓ Multi-use Transfer
- 11.5 – 90 litres per minute
- water
- diesels
- oils



SR



ACCESSORIES

Hoses page 91
Hose clips page 104

model	inlet (BSPF)	outlet (BSPF)	flow (l/min)	suction lift (mtrs)	head (mtrs)	w x l x h (mm)	weight (kgs)
Size 0	½"	½"	11.5	2.0	25	160x165x175	5.8
Size 1	¾"	¾"	17.3	2.0	25	180x195x205	7.1
Size 2	1"	1"	22.5	2.0	25	200x205x230	10.0
Size 3	1¼"	1¼"	25.0	2.0	25	240x232x275	12.3
Size 4	1¼"	1¼"	43.3	2.0	25	255x264x295	16.5
Size 5	1½"	1½"	53.5	2.0	25	275x276x320	20.7
Size 7	2"	2"	58.0	2.0	25	360x345x360	36.0